

C 1030 plus Art. 1862

GB Operating Instructions

Water Computer

F Mode d'emploi

Programmateur d'arrosage

NL Instructies voor gebruik

Besproegingscomputer

S Bruksanvisning

Bevattningscomputer

DK Brugsanvisning

Vandingscomputer

RUS Инструкция по эксплуатации

Компьютер для полива

GARDENA Water Computer C 1030 plus

Welcome to the Garden of GARDENA...



Translation of the original instructions from German.

Please read these operating instructions carefully and observe the notes given. Use these instructions to familiarise yourself with the Water Computer and its proper use as well as the notes on safety.



For safety reasons, children and young people under 16 as well as anyone who is not familiar with these operating instructions should not use the Water Computer.

→ Please keep these operating instructions in a safe place.

Contents

1. Where to Use Your GARDENA Water Computer	2
2. Safety Instructions	2
3. Function	3
4. Putting Your Water Computer into Operation	5
5. Programming	6
6. Putting Your Water Computer out of Operation	10
7. Maintenance	10
8. Troubleshooting	11
9. Available Accessories	11
10. Technical Data	12
11. Service / Warranty	12

1. Where to Use Your GARDENA Water Computer

Intended use:

The GARDENA Water Computer is intended for private use in domestic and hobby gardens, exclusively for outdoor use, to control sprinklers and watering systems.

The Water Computer can be used for automatic watering during holidays.

Please note:



The GARDENA Water Computer must not be used for industrial purposes or in conjunction with chemicals, foodstuffs, easily flammable and explosive materials.

2. Safety Instructions

Battery:

To ensure the Water Computer runs safely, only a 9V alkaline manganese battery (alkaline) type IEC 6LR61 must be used.

In order to stop the Water Computer from failing because of a weak battery if you are away for a long time, the battery must be replaced when the battery display still shows only 1 bar.

Setting up

Warning!

The Water Computer must not be used indoors.

→ Only use the Water Computer outdoors.

The Water Computer may only be set up vertically with the sleeve nut to the top to prevent water penetrating into the battery compartment.

The minimum water output to ensure that the Water Computer functions correctly is 20-30 l/h.

For example, at least 10 x 2-litre Drip Heads are required to control the Micro-Drip-System.

At high temperatures (over 60 °C at the display) the LCD display may extinguish. This does not affect the program in any way.

When the computer cools down the LCD display illuminates again.

The max. temperature for the water flow is 40 °C.

→ Only use clear fresh water.

The minimum operating pressure is 0.5 bar, the maximum operating pressure is 12 bar.

Avoid tensile strain.

→ Do not pull the hose connected to the Water Computer.

Programming

→ Program the Water Computer with the tap turned off.

In this way you can avoid getting wet when trying out the manual On/Off function (man. On/Off). You can remove the control unit from the housing to program the Water Computer.


If the controller is removed when the valve is open, the valve remains open until the controller is fitted again.

3. Function

With the Water Computer, the garden can be watered fully automatically up to 3 times a day at any time of day (every 8 hours). Sprinklers, a sprinkler system or a drip head watering system can be used for watering.

The Water Computer carries out watering fully automatically according to the set program and can therefore also be used during holidays. Early in the morning or late in the evening, evaporation and therefore water consumption is lowest.

Controls:



Display levels:

The watering programme is easily entered using the controls.

Control	Function
① Rotary button	Changes the adjustable values.
② OK button	Applies the values set with the rotary button.
③ Menu button	Changes to the next programme level.
④ Man. button	For switching the water throughput on or off manually.


The 6 display levels,

- Level 1: **Normal display**
- Level 2: **Current time and day of the week**
- Level 3: **Watering start time**
- Level 4: **Watering duration**
- Level 5: **Watering frequency**
- Level 6: **Switches programme on and off**

can be selected one after the other by pressing the **Menu** key.

You can change the display level at any time, even during programming. All the programme data which have been confirmed up to that point with the O.K. key are stored.

Display



Display


	Display	Description
⑤	Weekdays (Mo), (Tu), ...	Current weekday or programmed watering days.
⑥	Time	Flashes when in input mode for the current data (hours, minutes, day of the week).
⑦	am / pm	Display for 12 hour clock (e. g. in USA, Canada).
⑧	Start	Flashes when in input mode for watering start time.
⑨	Run Time	Watering duration (flashes when in input mode).
⑩	8h, 12h, 24h, 2nd, 3rd, 7th	Watering cycle (with drop symbol activated). Every 8 / 12 / 24 hours; every 2nd / 3rd / 7th day.
⑪	Prog ON / OFF	Watering programme on (ON) / off (OFF).
⑫	Automatic mode sensor	Watering is controlled automatically via the sensor.
⑬	Sensor ON / OFF	Sensor ON (watering) / Sensor OFF (watering is not carried out).
⑭	Battery	Indicates 5 battery levels: 3 bars: Battery fully charged 2 bars: Battery half full 1 bar: Battery low 1 bar flashing: Battery almost flat 0 bar: Battery flat

If no bars are displayed, the valve is no longer opened. **A valve opened by the programme will also close again if the battery is flat.** The battery display is reset when the battery is changed.

2 Bars	1 Bar	1 Bar flashing	0 Bar
Battery half full	Battery low	Battery almost flat	Battery flat
Valve opens.	Valve opens.	Valve still opens.	Valve does not open.
The Water Computer is guaranteed to work for a minimum of 4 more weeks.	The Water Computer will continue to work for no more than 4 weeks.	The Water Computer stops working soon.	The Water Computer stops working.
	It is advisable to change the battery.	The battery must be changed soon.	The battery must be changed.
	→ Replace battery (see 4. Putting Your Water Computer into Operation "Inserting battery").		

4. Putting Your Water Computer into Operation


Insert battery:



The Water Computer must only be operated with a 9 V alkali-manganese (alkaline) battery type IEC 6LR61.


1. Remove controller ⑯ from the housing of the Water Computer.

2. Insert battery in the battery compartment ⑯. **Observe correct polarity ⑰.** The display shows all the LCD-symbols for 2 seconds and then moves to the time/day of week level.



3. Install controller ⑯ on the housing again.

Connect Water Computer:



The Water Computer is fitted with a sleeve nut ⑰ for taps with (G 1") (33.3 mm) thread. The adaptor supplied ⑱ allows the Water Computer to be connected to taps with a (G ¾") thread (26.5 mm).

1. **For tap with a G ¾" (26.5 mm) thread:**

Screw adaptor ⑱ on to the tap manually (do not use pliers).


2. Screw sleeve nut ⑰ of the Water Computer on to the adaptor thread by hand (do not use pliers).

3. Screw tap connector ⑲ on to the Water Computer.

Connect soil moisture or rain sensor (optional):

Apart from scheduled watering there is also the option of including how damp the soil is or rainfall into the watering programme.

If the soil is damp enough, the programme will be stopped, or a programme will be prevented from starting. Manual operation via Man. On / Off is unaffected by this.




The "Soil moisture sensor-controlled watering" mode can only be selected when using a soil moisture sensor.

1. Remove controller ⑯ from the housing of the Water Computer.
2. Place soil moisture sensor **in** the watered area
— or —
place rain sensor (with extension cable if necessary)
outside the watered area.
3. Insert the sensor in the sensor connection ⑳ of the Water Computer.

An adapter cable may be required to connect older sensors, which can be purchased from GARDENA Service, **GARDENA Adapter cable Art. No. 1189-00.600.45.**

Fit anti-theft device (optional):



To secure your Water Computer against theft, you can obtain the **GARDENA Anti-theft device Art. No. 1815-00.791.00** from GARDENA Service.

1. Screw clamp ② with screw ② firmly to the back of the Water Computer.
2. Use clamp ① e.g. for fixing a chain.

It is no longer possible to remove the screw after it has been screwed in.

5. Programming

Set current time and day of week:

[Level 2]



To set the programme, the controller can be removed and mobile programming can be carried out (see 4. Putting Your Water Computer into Operation “*Inserting battery*”).

1. Press **Menu-key** (not necessary if the battery has just been inserted).
2. Set the time in hours with the rotary button (example: **9** hours) and confirm with the **OK-key**.
3. Set the time in minutes with the rotary button (example: **30** minutes) and confirm with the **OK-key**.
4. Set the day of the week with the rotary button (example: **Sa** Saturday) and confirm with the **OK-key**.

*The display moves to the message
Insert watering programme.*

Start and the hour display will flash on the screen.

Watering modes:

The water computer has 2 watering modes:

- **Scheduled watering** using the input programmes (watering starts depending on the watering start time)
- or –
- **Soil moisture sensor-controlled watering** using a GARDENA soil moisture sensor (watering begins when the soil moisture sensor registers dry).

Entering watering programme:


[Level 3]



[Level 4]



[Level 5]



Scheduled watering:

- Press **Menu**-key twice
(not necessary if the current time and day of the week has been entered).
Start Prog and the hours section flash on the display.
- Set the watering start time hours with the rotary button (E.g. **6**) and confirm with the **OK**-key.
Start Prog and the minute display flashes on the screen.
- Set the minutes for starting the watering time with the rotary button (example: **20** minutes) and confirm with the **OK**-key.
Run Time and the hours for the watering time flash on the display.
- Set the hours for the watering time with the rotary button (example: **0** hours) and confirm with the **OK**-key.
Run Time and minutes for the watering time flash on the display.
- Set watering time minutes with the rotary button (example: **10** minutes) and confirm with the **OK**-key.
Watering cycle **8h** flashes on the display.

The watering frequency can be selected by:

- the (6.) **watering cycle** (right hand column of the display)
— or —
 - the (7.) **watering days** (left hand column of the display).
- Select **watering cycle** with the rotary button (E.g. 2nd) and confirm by pressing **OK**.
8h / 12h / 24 h: Watering every 8 / 12 / 24 hours
2nd / 3rd / 7th: Watering every 2nd / 3rd / 7th day
 - The display jumps to the watering programme on the screen.*
 - or —
 - Select each **watering day** with the rotary button (E.g. Mo, Fr Monday and Friday) and confirm by pressing **OK**. Press the **Menu** button.
The display jumps to the watering programme on the screen.

Starting watering programmes:**[Level 6]**

The **Prog ON** must be selected so that the watering programme can start.

1. Press the **Menu** button 5 times (not necessary if the programme has been created before).
2. Select the **Prog ON** with the rotary button and confirm by pressing **OK**.

The Prog OK appears for 2 seconds and then the Normal display returns.

The water computer has now been programmed, i.e. the inbuilt valve opens and closes completely automatically and thus waters at the programmed time.

Even if **Prog OFF** is selected watering can be done manually.

Soil moisture sensor-controlled watering

Condition: the GARDENA Soil Moisture Sensor Art. 1188 is connected.

A previously set scheduled watering programme is retained but not carried out.



1. Hold the **Menu** button down for 5 seconds. *The watering cycle flashes.*

2. Select the required watering cycle with the rotary button (e.g. Day) and confirm with the **OK**-key.

Watering during the day (6 a.m. – 8 p.m.) when the soil moisture sensor registers dry.

Watering during the night (8 p.m. – 6 a.m.) when the soil moisture sensor registers dry.

Watering when the soil moisture sensor registers dry.

3. Set the watering duration in minutes (0 – 59 minutes) with the rotary button (E.g. 40 minutes) and confirm by pressing **OK**. *Watering starts in the set watering cycle as soon as the soil moisture sensor registers dry (Sensor ON).*

The watering duration set in the sensor-controlled watering mode also applies to manual watering.

In the case of soil moisture sensor-controlled watering, a two hour watering pause is triggered after every watering cycle in order for the soil moisture sensor to record the soil moisture.

Example:

Watering cycle = (Day),
watering duration = 40 minutes.

Watering begins when the sensor registers dry (Sensor ON) during the day (between 6 a.m. and 8 p.m.) and ends up to 40 minutes later depending on the amount of moisture in the soil.

The watering duration is preset to 30 minutes at the factory.

Emergency programme: If no sensor is inserted in sensor-controlled watering mode or if the connection cable is faulty, watering will take place every 24 hours. The watering duration depends on the run time but is limited to a maximum of 30 minutes.

Read / modify watering programmes:



If a value in the programme is to be changed, this can be changed without changing the other values in the programme.

1. Press the **Menu** key twice.
Start and the hours flash on the display.
2. Press the **Menu** button to jump to the next programme level
— or —
change the programme data with the rotary button and confirm by pressing the **OK** button.

When the watering duration is changed while a program is running, the current watering cycle is ended.

Manual operation:



The valve can be **opened or closed manually at any time**.

A program-controlled open valve can also be closed early without changing the program data (watering start time, watering duration and watering frequency).

The controller must be fitted.



1. Press **Man.-key** to open the valve manually (or to close an open valve).

Run Time and the watering time in minutes (set to **30** minutes in the works) flash for 10 seconds on the display.


2. Whilst the watering time in minutes is flashing, the watering duration can be modified with the rotary button (between **0:00** and **0:59**) (example: **10** minutes) and confirm with the **OK**-key.
3. Press **Man.-key** to close the valve early.
The valve is closed.

The amended manual opening period is stored, i.e. each time the valve is opened manually in future the modified opening period is preset. If the manual opening period is amended to **0:00**, the valve is closed and also remains closed after the **Man.-key** is pressed (child lock).

If the valve has been opened manually and a programmed start of a watering period overlaps the manual opening period, the programmed starting time is suppressed.

Example:

The valve is **opened at 9.00 a.m. manually**, the opening period is 30 minutes. A program with a **start time (START)** between **9.00 and 9.30 a.m.** will not be undertaken in this case.

Reset:

The factory settings are restored.

→ Press **Man.-key** and **Menu-key** simultaneously for 3 seconds.

All the LCD symbols are displayed for 2 seconds and the display moves to the normal display.

- All the program data are set to zero.
- The manual watering period is set to **0:30** again.
- The time and day of the week are retained.

Important information:

If no entry is made during programming for a period of more than 60 seconds, the normal display reappears. In this case all changes made up till now will be applied.

When a sensor installed in the water computer registers damp (**OFF**), the programmed watering is not carried out.

6. Putting Your Water Computer out of Operation

Storage / Overwintering:


1. Press **Menu-key** 5 times, select **Prog. OFF** with the rotary button and confirm with the **OK-key**.

The watering program is not run.

2. Store your Water Computer in a dry place where it is protected from frost.

Disposal:
(in accordance with RL 2002/96/EC)


The product must not be added to normal household waste. It must be disposed of in line with local environmental regulations.

- Important: Make sure that the unit is disposed of via your municipal recycling collection centre.

Disposing of flat batteries:


- Please return flat batteries to a GARDENA dealer or dispose of them properly at your nearest recycling centre.

Only dispose of batteries when they are **flat**.

7. Maintenance

Clean filter:

The filter ⑯ should be checked regularly and cleaned when necessary.



1. Unscrew sleeve nut ⑯ of the Water Computer by hand from the tap thread (do not use pliers).
2. If necessary unscrew the adaptor ⑯.
3. Remove filter ⑯ from sleeve nut ⑯ and clean.
4. Fit the Water Computer again (see 4. Putting Your Water Computer into Operation "Connecting Water Computer").

8. Troubleshooting

Fault	Possible Cause	Remedy
No display appears	Battery inserted incorrectly.	→ Check polarity markings match (+/-).
	Flat battery.	→ Insert new (alkaline) battery.
	Temperature on the display is higher than 60 °C.	Display appears after temperature has dropped.
Manual watering is not possible using the Man. button	Battery flat (1 bar flashes).	→ Insert new (alkaline) battery.
	Manual watering period is set to 0:00 .	→ Set manual watering period to a figure greater than 0:00 (see 5. Programming).
	Tap turned off.	→ Turn tap on.
Watering program is not being undertaken (no watering)	Watering program has not been entered completely.	→ Read off watering program and modify if necessary.
	Programs deactivated (Prog. OFF).	→ Activate program (Prog. ON).
	Program entry/modification during or just before the start pulse.	→ Make program entry/modification outside the programmed start times.
	Valve was opened manually previously.	→ Avoid possible program overlaps.
	Tap turned off.	→ Turn tap on.
	Soil moisture or rain sensor registers damp.	→ If dry, check setting/location of soil moisture/rain sensor.
	Battery flat (1 bar flashing).	→ Insert new (alkaline) battery.
	Minimum quantity of water drawn is less than 20 l/h.	→ Connect more drip heads.
Water Computer does not close	Sensor not correctly connected.	→ Check connection cable and sensor.
All 3 watering cycle symbols flash ()		



In the event of other faults please contact GARDENA Service.
Repairs should only be carried out by GARDENA service centres or dealers authorised by GARDENA.

9. Available accessories

GARDENA Soil Moisture Sensor	Art. No. 1188
GARDENA Rain Sensor electronic	Art. No. 1189
GARDENA Anti-theft device	Art. No. 1815-00.791.00 From GARDENA Service

GARDENA Adapter cable	To connect older GARDENA sensors	Art. No. 1189-00.600.45 From GARDENA Service
GARDENA Cable Adapter	For simultaneous connection of rain and soil moisture sensor	From GARDENA Service

10. Technical Data

Min./max. operating pressure:	0.5 bar / 12 bar
Flow medium:	Clear fresh water
Max. liquid temperature:	40 °C
Number of program-controlled watering cycles per day:	3 x (every 8 hrs.), 2 x (every 12 hrs.), 1 x (every 24 hrs.)
Number of program-controlled watering cycles per week:	Every day, every 2, 3 or 7 days; or individual selection of weekdays
Watering duration:	1 min. to 7 hours 59 min.
Battery required:	1 x 9 V alkaline manganese (alkaline) battery type IEC 6LR61
Operating time of the battery:	approx. 1 year

11. Service / Warranty

GARDENA guarantees this product for 2 years (from date of purchase). This guarantee covers all serious defects of the unit that can be proved to be material or manufacturing faults.

Under warranty we will either replace the unit or repair it free of charge if the following conditions apply:

- The unit must have been handled properly and in keeping with the requirements of the operating instructions.
- Neither the purchaser or a non-authorised third party have attempted to repair the unit.
- Faults which occur as a result of incorrectly installed or leaking batteries are not covered by the guarantee.
- Damage caused by frost is not covered by the warranty.

This manufacturer's guarantee does not affect the user's existing warranty claims against the dealer/seller.

If you have any problems with your Water Computer, please contact our Customer Service or return the defective unit together with a short description of the problem directly to one of the GARDENA Service Centres listed on the back of this leaflet.

GB EU Certificate of Conformity	Description of the unit: Désignation du matériel : Omschrijving van het apparaat : Produktbeskrivning : Beskrivelse af enhederne : Название устройства :	Water Computer Programmateur d'arrosage Besproeiingscomputer Bevattningscomputer Vandingscomputer Компьютер для полива
F Certificat de conformité aux directives européennes	Type : Type : Typ : Тип : Tip:	Art. No.: Référence : Art. nr.: Art. nr.: Varenr. : Арт. №:
The undersigned GARDENA International GmbH, Hans-Loreenser-Str. 40, D-89079 Ulm, hereby certifies that, when leaving our factory, the units indicated below are in accordance with the harmonised EU guidelines, EU standards of safety and product specific standards. This certificate becomes void if the units are modified without our approval.	C 1030 plus	1862
NL EU-overeenstemmingsverklaring	EU directives: Directives européennes : EU-richtlijnen: EU direktiv: EU Retningslinier: Директивы ЕС:	2004/108/EC
Ondergetekende GARDENA Manufacturing GmbH, Hans-Loreenser-Str. 40, D-89079 Ulm, bevestigt, dat het volgende genoemde apparaat in de door ons in de handel gebrachte uitvoering voldoet aan de eis van, en in overeenstemming is met de EU-richtlijnen, de EU-veiligheidsstandaard en de voor het product specifieke standaard. Bij een niet met ons afgestemde verandering aan het apparaat verliest deze verklaring haar geldigheid.	EU direktiv: EU Retningslinier: Директивы ЕС:	93/68/EC
S EU Tillverkarintyg	Year of CE marking: Date d'apposition du marquage CE : Installatiejaar van de CE-aanduiding: CE-Märkningsår: CE-Mærkningsår: Год разрешения маркировки значком СЕ :	2007
Undertecknad firma GARDENA International GmbH, Hans-Loreenser-Str. 40, D-89079 Ulm, intygar härmed att nedan nämnda produkter överensstämmer med EU:s direktiv, EU:s säkerhetstandard och produktsspecifikation. Detta intyg upphör att gälla om produkten ändras utan vårt tillstånd.	Ulm, 01.08.2007 Fait à Ulm, le 01.08.2007 Ulm, 01-08-2007 Ulm, 2007.08.01. Ulm, 01.08.2007 Ульм, 01.08.2007	Authorised representative Représentant légal Gemachtigte Behörig Firmatecknare Teknisk direktör Уполномоченный представитель
DK EU Overensstemmelse certifikat		
Undertegnede GARDENA International GmbH, Hans-Loreenser-Str. 40, D-89079 Ulm bekræfter hermed, at enhederne listet herunder, ved afsendelse fra fabrikken, er i overensstemmelse med harmoniserede EU retningslinjer, EU sikkerhedsstandarer og produktsspecifikationsstandarer. Dette certifikat træder ud af kraft hvis enhederne er ændret uden vor godkendelse.		
RUS Свидетельство о соответствии EC		
Мы, ниже подписьавшиеся GARDENA Manufacturing GmbH, Hans-Loreenser-Str. 40, D-89079 Ulm, настоящим подтверждаем, что нижеуказанное устройство, отгруженное с нашего предприятия, имеет исполнение, соответствующее требованиям согласованных директив ЕС, стандартам по технике безопасности ЕС и производственным стандартам. При несогласованном с нами изменении устройства настояще свидетельство теряет силу.	 Peter Lameli Vice President	

Deutschland / Germany	Croatia	Italy	Singapore
GARDENA Manufacturing GmbH Service Center Hans-Lorenser-Straße 40 D-89079 Ulm Produktfragen: (+49) 731 490-123 Reparaturen: (+49) 731 490-290 service@gardena.com	KLIS d.o.o. Stanciceva 79 10419 Vukovina Phone: (+385) 1 622 777 0 gardena@klis-trgovina.hr	GARDENA Italia S.p.A. Via Donizetti 22 20020 Lainate (Mi) Phone: (+39) 02.93.94.79.1 info@gardenaitalia.it	Hy - Ray PRIVATE LIMITED 40 Jalan Pemimpin #02-08 Tat Ann Building Singapore 577185 Phone: (+65) 6253 2277 hyray@singnet.com.sg
Argentina	Cyprus	Japan	Slovak Republic
Argensem® S.A. Calle Colonia Japonesa s/n (1625) Loma Verde Escobar, Buenos Aires Phone: (+54) 34 88 49 40 40 info@argensem.com.ar	FARMOKIPIKI LTD P.O. Box 7098 74, Digeni Akrita Ave. 1641 Nicosia Phone: (+357) 22 75 47 62 condam@spidernet.com.cy	KAKUICHI Co. Ltd. Sumitomo Realty & Development Kojimachi BLDG., 8F 5-1 Nibannocy, Chiyoda-ku Tokyo 102-0084 Phone: (+81) 33 264 4721 m_ishihara@kaku-ichi.co.jp	GARDENA Slovensko, s.r.o. Panónska cesta 17 851 04 Bratislava Phone: (+421) 263 453 722 info@gardena.sk
Australia	Czech Republic	Luxembourg	Slovenia
Nylex Consumer Products 50-70 Stanley Drive Somerton, Victoria, 3062 Phone: (+61) 1800 658 276 spare.parts@nylex.com.au	GARDENA spol. s r.o. Tuřanka 115 627 00 Brno Phone: (+420) 800 100 425 gardena@gardenabrnco.cz	Magasins Jules Neuberg 39, rue Jacques Stas Luxembourg-Gasperich 2549 Case Postale No. 12 Luxembourg 2010 Phone: (+352) 40 14 01 api@neuberg.lu	GARDENA d.o.o. Brodisce 15 1236 Trzin Phone: (+386) 1 580 93 32 servis@gardena.si
Austria / Österreich	Denmark	Netherlands	South Africa
GARDENA Österreich Ges.m.b.H. Stettnerweg 11-15 2100 Korneuburg Tel.: (+43) 22 62 7 45 45 36 kundendienst@gardena.at	GARDENA Norden AB Salgsafdeling Danmark Box 9003 S-200 39 Malmö info@gardena.dk	GARDENA Nederland B.V. Postbus 50176 1305 AD ALMERE Phone: (+31) 36 521 00 00 info@gardena.nl	GARDENA South Africa (Pty) Ltd. P.O. Box 11534 Vorna Valley 1686 Phone: (+27) 11 315 02 23 sales@gardena.co.za
Belgium	Finland	Neth. Antilles	Spain
GARDENA Belgium NV/SA Sterrebeekstraat 163 1930 Zaventem Phone: (+32) 2 7 20 92 12 Mail: info@gardena.be	Oy Husqvarna Ab Lautatarhankatu 8b / PL 3 FI-00581 HELSINKI	Jonka Enterprises N.V. Sta. Rosa Weg 196 P.O. Box 8200, Curaçao Phone: (+599) 9 767 66 55 pgm@jonka.com	GARDENA IBÉRICA S.L.U. C/Basauri, nº 6 La Florida 28023 Madrid Phone: (+34) 91 708 05 00 atencioncliente@gardena.es
Brazil	France	New Zealand	Sweden
Palash Comércio e Importação Ltda. Rua São João do Araguaia, 338 – Jardim Califórnia – Barueri – SP - Brasil – CEP 06409-060 Phone: (+55) 11 4198-9777 eduardo@palash.com.br	GARDENA PARIS NORD 2 69, rue de la Belle Etoile BP 57080 ROISSY EN FRANCE 95994 ROISSY CDG CEDEX Tél. (+33) 0826 101 455 service.consommateurs@ gardena.fr	NYLEX New Zealand Limited Building 2, 118 Savill Drive Mangere, Auckland Phone: (+64) 0800 22 00 88 spare.parts@nylex.com.au	GARDENA Norden AB Försäljningskontor Sverige Box 9003 200 39 Malmö info@gardena.se
Bulgaria	Great Britain	Norway	Switzerland / Schweiz
Хускварна България ЕООД 1799 София Бул. „Андрей Ляпчев“ № 72 Тел.: 02/ 8755148, 9753076 www.husqvarna.bg	Husqvarna UK Ltd Preston Road Aycliffe Industrial Park Newton Aycliffe County Durham DL5 6UP info.gardena@husqvarna.co.uk	GARDENA Norden AB Salgskontor Norge Kleverveien 6 1540 Vestby info@gardena.no	GARDENA (Schweiz) AG Bitziberg 1 8184 Bachenbülach Phone: (+41) 848 800 464 info@gardena.ch
Canada	Greece	Poland	Turkey
GARDENA Canada Ltd. 100 Summerlea Road Brampton, Ontario L6T 4X3 Phone: (+1) 905 792 93 30 info@gardenacanada.com	Agrokip Psomadopoulos S.A. Ifaistou 33A Industrial Area Koropi 194 00 Athens Greece V.A.T. EL093474846 Phone: (+30) 210 66 20 225 service@agrokip.gr	GARDENA Polska Sp. z o.o. Szymański 9 d 05-532 Baniocha Phone: (+48) 22 727 56 90 gardena@gardena.pl	GARDENA / Dost Diş Ticaret Mümessilik A.Ş. Sanayi Çad. Adil Sokak No. 1 Kartal - İstanbul Phone: (+90) 216 38 93 939 info@gardena-dost.com.tr
Chile	Hungary	Portugal	Ukraine / Україна
Antonio Martinic y Cia Ltda. Cassillas 272 Centro de Cassillas Santiago de Chile Phone: (+56) 2 20 10 708 garfar_cl@yahoo.com	GARDENA Magyarország Kft. Késmárk utca 22 1158 Budapest Phone: (+36) 80 20 40 33 gardena@gardena.hu	GARDENA Portugal Lda. Sintra Business Park Edifício 1, Fracção 0-G 2710-089 Sintra Phone: (+351) 21 922 85 30 info@gardena.pt	ALTSEST JSC 4 Petropavlivska Street Petropavlivska Borschahivka Town Kyivo Svyatoshyn Region 08130, Ukraine Phone: (+380) 44 459 57 03 upry@altsest.kiev.ua
Costa Rica	Iceland	Romania	USA
Compania Exim Euroiberoamericana S.A. Los Colegios, Moravia, 200 metros al Sur del Colegio Saint Francis - San José Phone: (+506) 297 68 83 exim_euro@racsa.co.cr	Ó. Johnson & Kaaber Tunguhalsi 1 110 Reykjavík ooj@okj.is	MADEX INTERNATIONAL SRL Soseaua Odaii 117-123, Sector 1, Bucuresti, RO 013603 Phone: (+40) 21 352 76 03 madex@ines.ro	Melnor Inc. 3085 Shawnee Drive Winchester, VA 22604 Phone: (+1) 540 722-9080 service_us@melnor.com
Russia / Россия	Ireland	Russia / Россия	
OOO ГАРДЕНА РУС 123007, г. Москва Хорошевское шоссе, д. 32а Тел.: (+7) 495 540 99 57 info@gardena-rus.ru	Michael McLoughlin & Sons Hardware Limited Long Mile Road Dublin 12	ООО ГАРДЕНА РУС 123007, г. Москва Хорошевское шоссе, д. 32а Тел.: (+7) 495 540 99 57 info@gardena-rus.ru	1862-28.960.02 / 0208 © GARDENA Manufacturing GmbH D-89070 Ulm http://www.gardena.com